

What is Claimed Is:

1. An apparatus for cleaning paint spray gun assemblies, comprising:

a holding tank for holding a supply of clean solution;

a first distillation chamber including an access opening;

a second distillation chamber, including an access opening;

a wash basin moveably supported on said apparatus and adapted to be selectively positionable in fluid transferring communication with either of said first and second distillation chambers;

a pump for delivering the clean solution from said holding tank to said wash basin for discharge therein, wherein solution discharged into the wash basin returns to the selected distillation chamber positioned in fluid transfer communication with said wash basin;

heaters associated with each of said first and second distillation chambers for heating contaminated solution contained therein in order to produce vapors and separate contaminants; and

a condenser for condensing the vapors to yield purified solution, said condenser being disposed in fluid communication with said holding tank for directing the purified solution to said holding tank.

2. The apparatus as recited in Claim 1 wherein said washbasin is moveable for selective alignment with the access opening of either of said first and second distillation chambers so that solution discharged into the

washbasin is directed through the access opening and into the respective distillation chamber selectively positioned in fluid transfer communication with the wash basin.

3. The apparatus as recited in Claim 1 further comprising:
access doors for selectively covering and sealing closed the access openings of said first and second distillation chambers.

4. The apparatus as recited in Claim 1 further comprising:
a second pump for circulating the solution from either of said first or second distillation chambers and to said wash basin for discharge therein.

5. The apparatus as recited in Claim 1 wherein said wash basin includes a hood structure and closeable access door for surrounding and enclosing the washbasin in order to contain sprayed cleaning solution, contaminants and vapors during cleaning of the paint spray gun assemblies placed within the wash basin.

6. The apparatus as recited in Claim 4 wherein said wash basin includes a hood structure and closeable access door for surrounding and enclosing the washbasin in order to contain sprayed cleaning solution, contaminants and vapors during cleaning of the paint spray gun assemblies placed within the wash basin.

7. The apparatus as recited in Claim 6 wherein said second pump is operable for a timed wash cycle to thereby discharge the solution into said wash basin, under pressure, during the timed wash cycle.

8. The apparatus as recited in Claim 1 wherein said wash basin is moveable supported on a transverse rail.